

BOLA REMOTE RESTRAINT WRAP

BolaWrap is the only remote response to resistance tool that ensures a safe space between subject and officer, does not rely on pain compliance, and is specifically designed to be deployed early in an engagement.

Inflicting pain often escalates encounters, BolaWrap's non-threatening form allows time to de-escalate and provide needed support.



**Early Restraint.
Remote Restraint.
Safer Restraint.**

REQUEST TRAINING OR A QUOTE

info@wraptechnologies.com

800-583-2652

BOLAWRAP.COM











Product Elements

- A. Cocking Lever
- B. Green Line Laser
- C. Activation Button
- D. Safety
- E. Cartridge Release Lever
- F. Propellant
- G. Serialized Cartridge
- H. Kevlar Cord
- I. Anchor
- J. Hooks

Product Features

- Discharge Speed: 513 ft per second (156 meters per second)
- Wrap Speed: 270 ft per second at 10 ft (82 meters per second at 3 meters)
- Distance: 10-25 feet (3-8 meters)
- Sound volume: 105/110 dB
- Wrap: Wraps around body 1-3 times
- Reload Time: 3-8 seconds
- Laser: green line laser for accuracy
- Bola Cord: Recyclable, 8' Kevlar® (2.4 meters), 380 pound strength
- Entangling Barbs: 4 per anchor
- Propellant: .380 partial charge blank
- US Usage: 35+ states
- International Usage: Delivered to more than 10 countries

Product Benefits

- | | | | |
|--|--|--|---|
|  <p>Small
designed to restrain without use of pain to gain compliance</p> |  <p>Effective
Remote restraint aids in controlling subjects</p> |  <p>Simple
Simple to deploy, minimum training required</p> |  <p>Accurate
Wide latitude of accuracy at a range of 10-25 feet</p> |
|  <p>Flexible
Other use of force options remain available</p> |  <p>Safe
designed to restrain without use of pain to gain compliance</p> |  <p>Durable
Weather resistant vand rugged</p> |  <p>Quick Refresh
Rapid cartridge refresh to support multiple wraps</p> |

WARNING: FOR PROFESSIONAL LAW ENFORCEMENT & MILITARY USE ONLY. REFER TO INSTRUCTIONS MANUAL.